AGC	CE Marking of Mirrors from silver-coated float glass for internal use EN 1036-2:2008 Declaration of performances Mirox MNGE Clearvision	CE

We

AGC Glass Europe
Building Division
Chaussée de La Hulpe 166 - B 1170 Brussels
Tel.: + 32 - (0) 2 674.31.11 - Fax: + 32 - (0) 2 674.44.62

Declare, under his sole responsibility, the following characteristics for the CE Marking of the glass products named **MIROX MNGE CLEARVISION,** intended to be used in buildings and construction works, following **EN 1036-2:2008**

	Mirox MNGE Clearvision characteristics in :	**AVCP Systems**	**3 mm**	**4 mm**	**5 mm**	**6 mm**	**8 mm**
1.	Resistance to fire (EN 13501-2)	1	NPD	NPD	NPD	NPD	NPD
2.	Reaction to fire (EN 13501-1)	3, 4	A2-s1, d0	A2-s1, d0	A2-s1, d0	A2-s1, d0	A2-s1, d0
3.	External fire performances	3, 4	NPD	NPD	NPD	NPD	NPD
4.	Bullet resistance (EN 1063)	1	NPD	NPD	NPD	NPD	NPD
5.	Explosion resistance (EN 13541)	1	NPD	NPD	NPD	NPD	NPD
6.	Burglar resistance (EN 356)	3	NPD	NPD	NPD	NPD	NPD
7.	Pendulum body impact resistance (EN 12600)	3	NPD	NPD	NPD	NPD	NPD
8.	Resistance against sudden temperature change and temperature differentials	4	NPD	NPD	NPD	NPD	NPD
9.	Wind, snow, permanent and imposed load resistance	4	NPD	NPD	NPD	NPD	NPD
10.	Direct airborne sound reduction (EN 12758): Rw (C;Ctr)	3	NPD	NPD	NPD	NPD	NPD
11.	U-value (EN 673)	3	5,8	5,8	5,8	5,7	5,7
12.	Light transmission/reflection (EN 410): τ_v / ρ_v / ρ'_v	3	NPD	NPD	NPD	NPD	NPD
13	- Solar transmission/reflection/factor (EN 410): τ_e / ρ_e / ρ'_e - Solar factor: g	3	NPD NPD	NPD NPD	NPD NPD	NPD NPD	NPD NPD
14.	Durability	3	PASS	PASS	PASS	PASS	PASS

Brussels
10th of September 2013

E. Ceriani
Primary Sales & Strategic, Marketing Director, Building